In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in this application:

Claims 1-18 (cancelled)

19. (Currently amended) A method of changing the combination of a lock, said method comprising the step of:

inserting a key into a key cylinder of the lock;

rotating said key, such that said key cylinder is rotated from a first position to a second position;

rotating a <u>user graspable</u> number dial relative to a <u>user graspable</u> tumbler dial; <u>and</u> turning the key <u>and the key cylinder</u> back to the <u>locked_first</u> position.

wherein the lock remains locked while the combination is changed.

- 20. (Currently amended) The method set forth in claim 19 wherein the step of rotating the key further comprising comprises decoupling the number dial from the tumbler dial.
- 21. (Currently amended) The method set forth in claim 19 wherein the key cylinder is mounted in a-the tumbler dial at a position offset from the rotational center of the tumbler dial.
- 22. (Previously presented) The method set forth in claim 19 wherein at least ten combination changes are available.
- 23. (Previously presented) The method as set forth in claim 19 further comprising the step of aligning a marking with a number on said number dial, wherein said number correlates to a combination to unlock the lock.

Claims 24-31 (cancelled)

32. (New) The method set forth in claim 19, wherein the lock remains locked while the combination is changed.